NSN 5305-01-400-5792

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-400-5792

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.370 inches
Fastener Length:
Between 0.605 inches and 0.635 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.456 inches and 0.508 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Minimum Yield Strength:
95000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response and ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas7504 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-400-5792

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0