NSN 5305-01-405-9919

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-405-9919 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.307 inches and 0.317 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.085 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.313 inches Point Style: Cone **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-405-9919

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0