## NSN 5305-01-406-1656

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-406-1656 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.310 inches **Fastener Length:** Between 3.690 inches and 3.750 inches **Head Style:** Pan **Head Diameter:** 0.275 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** 0.112 inches **Second Diameter From Head:** 0.124 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.540 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 3.440 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment:** Passivate

**-**4 P O

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unc

## NSN 5305-01-406-1656

Externally Relieved Body Screw - Page 2 of 2



Shelf	Life:
•	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0