NSN 5305-01-406-3368

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-406-3368 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** 0.500 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** 0.075 inches **Point Style:** Cone **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed standard no 66 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-406-3368

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.