NSN 5305-01-406-3382

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-406-3382 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.375 inches **Fastener Length:** Between 1.985 inches and 2.015 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.625 inches and 0.640 inches **Head Height:** Between 0.678 inches and 0.698 inches Point Length: Between 0.235 inches and 0.265 inches **Point Diameter:** Between 0.270 inches and 0.280 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees Material: Stainless steel **Material Specification:** Qq-s-637 federal specification single material response or astm-108 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072c military specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

NSN 5305-01-406-3382

Externally Relieved Body Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072c spec.