Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-406-5450

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.213 inches and 0.223 inches
Fastener Length:
Between 0.406 inches and 0.437 inches
Head Style:
Flat countersunk
Head Diameter:
0.225 inches
First Diameter From Head:
Between 0.073 inches and 0.083 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.219 inches
Point Style:
Cone
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Specification:
Fed standard 66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-406-5450

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0