

View Online at <https://aerobasegroup.com/nsn/5305-01-406-7488>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.417 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.244 inches and 0.279 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

82.0 degrees

**Screw Material:**

Steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 302

**Screw Material Specification:**

66 federal standard all material responses

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Special Features:**

Epoxy color coat head, mil-e-15090, type iii, cl 2, or color grey no. 26307, fed-std-595

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5002 spec.