NSN 5305-01-406-8174



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-406-8174 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.230 inches **Fastener Length:** Between 0.280 inches and 0.310 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.333 inches and 0.385 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 100.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 304 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Special Features:** Epoxy color coat head, mil-e-15090, type iii, class 2; or color no. 26307 fed-std-595 color grey **Thread Series Designator:** Unf

Passivate

Screw Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Special Features:

Epoxy color coat head, mil-e-15090, type iii, class 2; or color no. 26307 thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

-
Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-406-8174

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.