NSN 5305-01-407-3472



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-407-3472 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.560 inches **Fastener Length:** 0.680 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.242 inches and 0.252 inches Width Between Flats: Between 0.418 inches and 0.438 inches **Extended Washer Diameter:** 0.380 inches **Extended Washer Thickness:** Between 0.055 inches and 0.065 inches **Spline Major Diameter:** 0.287 inches **Washer Quantity: Internal Drive Style:** Torx **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 40.0 rockwell c primary washer and 48.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.560 inches and 0.580 inches **Primary Washer Style:** Spring tension **Primary Washer Material Thickness:** Between 0.030 inches and 0.040 inches **Special Features:** Sealing compound black pvc (pm-118) certified to fbms 6-10 ty. 1-b Material:

Steel primary washer **Surface Treatment:** Dichromate zinc

NSN 5305-01-407-3472

Assembled Washer Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0