Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-407-7252

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.250 inches
Fastener Length:
0.800 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.262 inches and 0.270 inches
Head Height:
Between 0.159 inches and 0.164 inches
First Diameter From Head:
0.115 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.550 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.164 inches
Width Across Flats:
Between 0.140 inches and 0.142 inches
Thready Qty Per Inch (tpi):
32
Externally Relieved Body Diameter Quantity:
1
Special Features:
M/f ms16995-29; threaded portion under head 0.050 lg
Material:
Steel comp 384 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0