NSN 5305-01-407-7253

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-407-7253 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.242 inches **Fastener Length:** 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.4640 inches and 0.5066 inches First Diameter From Head: Between 0.200 inches and 0.204 inches **Internal Drive Style:** High-torque **End Application:** Aircraft, hawkeye e-2c **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** M/f nas1604-3; unthreaded shoulder portion under head 0.250 in.Dia Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-407-7253

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0