NSN 5305-01-407-9493

N/a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-407-9493

Thread Class
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
1.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
Hardness Rating:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator:
Hardness Rating: 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response and ams 5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 ty2 cl2 federal specification single treatment response Thread Series Designator: Unrc

NSN 5305-01-407-9493

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0