NSN 5305-01-408-0445

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-408-0445 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Hole Diameter:** Between 0.034 inches and 0.042 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Titanium alloy uns r56400 **Screw Material Specification:** Ams4967 assn standard single material response **Screw Surface Treatment:** Aluminum and chromate **Screw Surface Treatment Specification:** Mil-c-83488, tyii, cl3 military specification single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1101 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-408-0445

Machine Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-83488 spec.