NSN 5305-01-408-1967

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-408-1967 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.176 inches and 0.196 inches **Fastener Length:** 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.078 inches and 0.088 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.429 inches and 0.446 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Color: Black Material: Stainless steel **Material Specification:** Fed 66 300 series federal standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-408-1967

Externally Relieved Body Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.