Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-408-4805

Thread Class: 2a 2a Thread Direction: Right-hand Thread Length: Between 0.210 inches and 0.225 inches Fastener Length: Between 0.445 inches and 0.475 inches Head Style: Flat countersunk Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Yup Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mif ms24693-c28 Materia: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: N/a	
Thread Direction: Right-hand Thread Length: Between 0.210 inches and 0.225 inches Fastener Length: Between 0.445 inches and 0.475 inches Head Style: Flat countersunk Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 9.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mtf ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Class:
Right-hand Thread Length: Between 0.210 inches and 0.225 inches Fastener Length: Between 0.445 inches and 0.475 inches Head Siyle: Flat countersunk Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Vier Pron (tpi): 32 Countersink Angle: Between 9.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mtf ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	
Tread Length: Between 0.210 inches and 0.225 inches Fastener Length: Between 0.445 inches and 0.475 inches Head Style: Flat countersunk Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Stel comp 302 or stel comp 303 or stel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	
Between 0.210 inches and 0.225 inchesFastener Length:Between 0.445 inches and 0.475 inchesHead Style:Flat countersunkHead Diameter:Between 0.238 inches and 0.279 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThread Diameter:0.138 inchesThread Pienere:0.318 inchesBetween 9.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:Mif ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	-
Fastener Length:Between 0.445 inches and 0.475 inchesHead Style:Flat countersunkHead Diameter:Between 0.238 inches and 0.279 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Countersink Angle:Between 9.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:Mt ms24693-c28Material:Stel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	
Between 0.445 inches and 0.475 inches Head Style: Flat countersunk Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mt ms24693-c28 Material: Stel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	
Head Style:Flat countersunkHead Diameter:Between 0.238 inches and 0.279 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThread Vaty Per Inch (tpi):32Contersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:Mr ms24693-c28Material:Stele Comp 302 or stele comp 303 or stele comp 304Fursead Series Designator:UncShelf Life:N/a	Fastener Length:
Flat countersunkHead Diameter:Between 0.238 inches and 0.279 inchesFirst Diameter From Head:Between 0.100 inches and 0.105 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Countersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:Mrd ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateIncShelf Life:N/a	Between 0.445 inches and 0.475 inches
Head Diameter: Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mf ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Head Style:
Between 0.238 inches and 0.279 inches First Diameter From Head: Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: Mrf ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Flat countersunk
First Diameter From Head:Between 0.100 inches and 0.105 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Countersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:Mt ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateIncad Series Designator:UncShelf Life:N/a	Head Diameter:
Between 0.100 inches and 0.105 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Between 0.238 inches and 0.279 inches
Internal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Countersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:M/f ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	First Diameter From Head:
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Between 0.100 inches and 0.105 inches
Thread Diameter:0.138 inchesThready Qty Per Inch (tpi):32Countersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:1Special Features:M/f ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateInread Series Designator:UncShelf Life:N/a	Internal Drive Style:
0.138 inches Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Cross recess type 1
Thready Qty Per Inch (tpi): 32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Thread Diameter:
32 Countersink Angle: Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	0.138 inches
Countersink Angle:Between 99.0 degrees and 101.0 degreesExternally Relieved Body Diameter Quantity:11Special Features:M/f ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	Thready Qty Per Inch (tpi):
Between 99.0 degrees and 101.0 degrees Externally Relieved Body Diameter Quantity: 1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	32
Externally Relieved Body Diameter Quantity:1Special Features:M/f ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	Countersink Angle:
1 Special Features: M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life:	Between 99.0 degrees and 101.0 degrees
Special Features:M/f ms24693-c28Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	Externally Relieved Body Diameter Quantity:
M/f ms24693-c28 Material: Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	1
Material:Steel comp 302 or steel comp 303 or steel comp 304Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/a	Special Features:
Steel comp 302 or steel comp 303 or steel comp 304 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	M/f ms24693-c28
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a	Material:
Passivate Thread Series Designator: Unc Shelf Life: N/a	Steel comp 302 or steel comp 303 or steel comp 304
Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment:
Unc Shelf Life: N/a	Passivate
Shelf Life: N/a	Thread Series Designator:
N/a	Unc
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
	-
Demilitarization:	Demilitarization:
No	No
Fiig:	Fiig:
A003b0	A003b0