NSN 5305-01-408-7072

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-408-7072

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.357 inches and 0.440 inches
Fastener Length:
0.440 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.313 inches
Internal Drive Style:
Tri-wing recess
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
63.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas6003 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-408-7072

Machine Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A500d0