

View Online at <https://aerobasegroup.com/nsn/5305-01-408-7072>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.357 inches and 0.440 inches

Fastener Length:

0.440 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

Between 0.305 inches and 0.313 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Iron alloy 660

Screw Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

63.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas6003 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0