

View Online at <https://aerobasegroup.com/nsn/5305-01-408-7073>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.357 inches and 0.440 inches

**Fastener Length:**

0.440 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.080 inches and 0.095 inches

**Width Between Flats:**

Between 0.243 inches and 0.251 inches

**Internal Drive Style:**

Tri-wing recess

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Steel comp e4340 or steel comp 8740

**Screw Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5000 spec.