## NSN 5305-01-408-7119

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-408-7119

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.442 inches and 0.500 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Patch
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32  Min. Tensile Strength (psi): 35000 pounds per square inch
32 Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Min. Tensile Strength (psi): 35000 pounds per square inch Screw Material: Stainless steel Locking Feature Material: Plastic polyamide Screw Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: