Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-409-0196

Thread	Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Fastener Length:

1.125 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.375 inches

Head Height:

Between 0.244 inches and 0.250 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.187 inches and 0.190 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 42.0 rockwell c

Minimum Yield Strength:

120000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp xm-7 or steel comp 316 or steel comp 384

Material Specification:

Astm a493 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-409-0196

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

