
Socket Head Cap Screw - Page 1 of 2





| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 1.810 inches and 2.500 inches |
| Fastener Length: |
| Between 5.940 inches and 6.000 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.550 inches and 0.562 inches |
| Head Height: |
| Between 0.366 inches and 0.375 inches |
| Locking Feature: |
| Patch threads or strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.375 inches |
| Width Across Flats: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 16 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Material: |
| Plastic polyamide locking feature |
| Material Specification: |
| Qq-n-281 federal specification single material response fastener |
| Thread Series Designator: |
| Unrc |
| Specification Or Standard: |
| 2 type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-409-0300

Socket Head Cap Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-f-18240 spec.