

View Online at <https://aerobasegroup.com/nsn/5305-01-409-0899>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.170 inches and 0.210 inches

Fastener Length:

Between 0.594 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Washer Quantity:

1

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.109 inches and 0.111 inches

Features Provided:

Dry film lubricant

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Minimum Yield Strength:

90000 pounds per square inch

Primary Washer Outside Diameter:

Between 0.262 inches and 0.282 inches

Primary Washer Style:

Flat

Primary Washer Material Thickness:

Between 0.016 inches and 0.020 inches

Material:

Steel primary washer

Material Specification:

Qq-s-766, 300 series assn standard all material responses primary washer

Surface Treatment:

Passivate primary washer

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response primary washer

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0