NSN 5305-01-410-6626

Thread Class:

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-410-6626

2a
Thread Direction:
Right-hand
Thread Length:
Between 0.170 inches and 0.210 inches
Fastener Length:
Between 0.531 inches and 0.562 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Washer Quantity:
1
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Features Provided:
Dry film lubricant
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Minimum Yield Strength:
90000 pounds per square inch
Primary Washer Outside Diameter:
Between 0.262 inches and 0.282 inches
Primary Washer Style:
Flat
Primary Washer Material Thickness:
Between 0.016 inches and 0.020 inches
Material:
Steel primary washer
Material Specification:
0 700,000 : () ! !! !! !!

Surface Treatment:Passivate primary washer

Qq-s-766 300 series federal specification all material responses primary washer

NSN 5305-01-410-6626

Assembled Washer Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response primary washer

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0