

View Online at <https://aerobasegroup.com/nsn/5305-01-410-6626>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.170 inches and 0.210 inches

**Fastener Length:**

Between 0.531 inches and 0.562 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.218 inches and 0.226 inches

**Head Height:**

Between 0.134 inches and 0.138 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.109 inches and 0.111 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Minimum Yield Strength:**

90000 pounds per square inch

**Primary Washer Outside Diameter:**

Between 0.262 inches and 0.282 inches

**Primary Washer Style:**

Flat

**Primary Washer Material Thickness:**

Between 0.016 inches and 0.020 inches

**Material:**

Steel primary washer

**Material Specification:**

Qq-s-766 300 series federal specification all material responses primary washer

**Surface Treatment:**

Passivate primary washer

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response primary washer

**Thread Series Designator:**

Unrc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0