## NSN 5305-01-410-6629

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-410-6629 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.313 inches **First Diameter From Head:** Between 0.235 inches and 0.245 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.600 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity: Special Features:** M/f ms16996-32 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-410-6629

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0