## NSN 5305-01-410-6630

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-410-6630 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.410 inches **Fastener Length:** 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.190 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.370 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Special Features:** M/f nas1351c4-28 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-410-6630

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0