## NSN 5305-01-411-2895

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-411-2895

view Offiline at https://derobasegroup.com/nsii/5505-01-411-2055
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.407 inches and 0.500 inches
Fastener Length:
Between 0.469 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.110 inches
Hole Diameter:
0.038 inches
Internal Drive Style:
Torque set
End Application:
F-16
Thread Diameter:
0.190 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Screw Material Specification:
Mil-s-5652 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-01-411-2895

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5652 spec.