NSN 5305-01-411-2895

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-411-2895



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.407 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.110 inches Hole Diameter: 0.038 inches Internal Drive Style: Torque set **End Application:** F-16 **Thread Diameter:** 0.190 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Screw Material Specification:** Mil-s-5652 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

NSN 5305-01-411-2895

Machine Screw - Page 2 of 2

Fiig: A500d0

Mil-std (military Standard):

Mil-s-5652 spec.

