NSN 5305-01-411-4799

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-411-4799 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.215 inches **Fastener Length:** Between 0.450 inches and 0.480 inches **Head Style:** Pan **Head Diameter:** 0.270 inches **Head Height:** 0.097 inches **First Diameter From Head:** 0.090 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.255 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Iron alloy 660 is heat treat to 24 - 37 hrc, steel comp 615 heat treat to 32 - 38 hrc, or steel 630 heat treat to 31 - 39 hrc Material: Iron alloy 660 or steel comp 615 or steel comp 630 **Material Specification:** Ams5735 assn standard 1st material response or ams5616 assn standard 2nd material response or ams5643 assn standard 3rd material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35, ty i federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

--

N/a

Unit Of Measure:

NSN 5305-01-411-4799

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0