A003b0

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-411-4811

Thread Class: 2a Fastener Length: 0.562 inches Head Style: Flat chamfer First Diameter From Head: Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Fastener Length:0.562 inchesHead Style:Flat chamferFirst Diameter From Head:Between 0.062 inches and 0.065 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.330 inchesInternal Drive Style:SlotThread Diameter:0.086 inchesThready Qty Per Inch (tpi):56Externally Relieved Body Diameter Quantity:1
0.562 inches Head Style: Flat chamfer First Diameter From Head: Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Head Style: Flat chamfer First Diameter From Head: Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Flat chamfer First Diameter From Head: Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
First Diameter From Head: Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Between 0.062 inches and 0.065 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
0.330 inches Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Internal Drive Style: Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Slot Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Thread Diameter: 0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
0.086 inches Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
Thready Qty Per Inch (tpi): 56 Externally Relieved Body Diameter Quantity: 1
56 Externally Relieved Body Diameter Quantity: 1
Externally Relieved Body Diameter Quantity:
1
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: