## NSN 5305-01-412-1449

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-412-1449 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.107 inches **Fastener Length:** 0.188 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.058 inches and 0.068 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.209 inches **Secondary Washer Outside Diameter:** Between 0.213 inches and 0.223 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.025 inches **Secondary Washer Material Thickness:** Between 0.013 inches and 0.019 inches Material: Copper alloy **Surface Treatment:** Tin

Thread Series Designator: Unc

## NSN 5305-01-412-1449

Assembled Washer Screw - Page 2 of 2



| Spec | ifica | tion | Data: |
|------|-------|------|-------|
|------|-------|------|-------|

80205-nas720 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0