NSN 5305-01-412-1739

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-412-1739 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** Between 0.745 inches and 0.755 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.158 inches and 0.164 inches **First Diameter From Head:** Between 0.130 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.375 inches and 0.380 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.1415 inches and 0.1417 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-412-1739

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0