NSN 5305-01-412-5991

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-412-5991

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.323 inches |
| Fastener Length: |
| Between 1,433 inches and 1,463 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Locking Feature: |
| Pellet threads or patch threads or pellet threads |
| Grip Diameter: |
| Between 0.1890 inches and 0.1895 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 1.115 inches and 1.135 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas7803 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-412-5991

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

