## NSN 5305-01-413-4583

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-413-4583 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.594 inches **Fastener Length:** Between 1.856 inches and 1.903 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.826 inches and 0.884 inches **Grip Diameter:** Between 0.4677 inches and 0.4682 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.437 inches **Grip Length:** Between 1.803 inches and 1.823 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

Unit Of Measure:

N/a

## NSN 5305-01-413-4583

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0