NSN 5305-01-414-0262

Thread Class:

Thread Direction:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-414-0262

Right-hand
Thread Length:
1.000 inches
Fastener Length:
0.875 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.093 inches and 0.097 inches
Hole Quantity:
Hole Quantity: 2
-
2
2 Hole Type:
2 Hole Type: Drilled
2 Hole Type: Drilled Thready Qty Per Inch (tpi):
2 Hole Type: Drilled Thready Qty Per Inch (tpi): 40
2 Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi):
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating:
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength:
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Hole Configuration Style:
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Hole Configuration Style: Round internal hexagon
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Hole Configuration Style: Round internal hexagon Product Name:
Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Hole Configuration Style: Round internal hexagon Product Name: (inavy) screw, cap, socket head

Fed 66 federal standard all material responses

NSN 5305-01-414-0262

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0