## NSN 5305-01-414-2948

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-414-2948 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.089 inches and 0.125 inches **Fastener Length:** 0.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.155 inches and 0.165 inches **Head Height:** Between 0.028 inches and 0.036 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 316 **Screw Material Specification:** Fed 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Altered item drawing from p/n's ms51959-1 and 418198-1 nsn 5305007662422 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-01-414-2948

Machine Screw - Page 2 of 2



Fiig:

A500d0