NSN 5305-01-414-4166

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-414-4166

view offilite at https://aerobasegroup.com/nsii/05005-01-414-4100
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
1.000 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Locking Feature:
Strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mi; l-s-6049 military
specification 3rd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Specification Data:
80205-nas1191 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-414-4166

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.