## NSN 5305-01-414-4197

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-414-4197 **Thread Class:** 2a **Fastener Length:** Between 0.382 inches and 0.392 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.147 inches and 0.170 inches First Diameter From Head: Between 0.051 inches and 0.061 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.167 inches and 0.177 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** 82.0 degrees **Externally Relieved Body Diameter Quantity: Special Features:** Altered from nsn 5305007633357, 5305007254191 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Fed 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-414-4197

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0