## NSN 5305-01-415-1283

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-415-1283



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.438 inches and 0.500 inches Fastener Length: Between 0.469 inches and 0.500 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches Locking Feature: Pellet **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response Locking Feature Material Specification: Mil-f-18240 military specification single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

---

## NSN 5305-01-415-1283

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.

