## NSN 5305-01-416-1267

Machine Screw - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5305-01-416-1267

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
0.688 inches	
Fastener Length:	
Between 0.658 inches	s and 0.688 inches
Head Style:	
Pan no. 2	
Head Diameter:	
Between 0.256 inches	s and 0.270 inches
Head Height:	
Between 0.087 inches	s and 0.097 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Features Provided:	
Boot type washer	
Thready Qty Per Inc	h (tpi):
32	
Min. Tensile Strengt	h (psi):
160000 pounds per s	quare inch
Screw Material:	
Steel comp 4140 or s	eel comp 4340 or steel comp 8740
Screw Material Spec	ification:
Mil-s-5626 military sp	ecification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd mate	rial response
Head Surface Treatr	nent:
Plastic epoxy	
Screw Surface Treat	ment:
Cadmium and chroma	ate
Screw Surface Treat	ment Specification:
Qq-p-416 type 2 cl 3	federal specification single treatment response
Special Features:	
Head and nylon wash	er color: black
Thread Series Desig	nator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5305-01-416-1267

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

