NSN 5305-01-416-1268



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-416-1268 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches **Features Provided:** Boot type washer Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Head Surface Treatment:** Plastic epoxy **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Special Features:** Head and nylon washer color: black **Thread Series Designator:** Unc Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-416-1268

Machine Screw - Page 2 of 2



Demi			

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.