## NSN 5305-01-416-5248

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-416-5248 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.569 inches and 0.619 inches **Fastener Length:** Between 1.267 inches and 1.297 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.722 inches and 0.740 inches **Head Height:** Between 0.206 inches and 0.220 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.375 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1578 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-01-416-5248

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.