

View Online at <https://aerobasegroup.com/nsn/5305-01-416-5254>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.363 inches

**Fastener Length:**

Between 0.848 inches and 0.878 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.2578 inches and 0.3047 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 and steel comp 4340 and steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.