## NSN 5305-01-416-5348

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-416-5348 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.316 inches **Fastener Length:** Between 0.426 inches and 0.456 inches **Head Style:** Flat countersunk **Head Diameter:** 0.449 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.250 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1154 professional/industrial association standard Shelf Life: **Unit Of Measure:** 

N/a
Unit Of Measure:
-Demilitarization:
No

## NSN 5305-01-416-5348

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0