## NSN 5305-01-416-7381

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-416-7381 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.120 inches **Fastener Length:** 0.344 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.246 inches and 0.254 inches **Head Height:** Between 0.115 inches and 0.135 inches **Shoulder Diameter:** 0.1235 inches first shoulder and 0.1245 inches first shoulder **Shoulder Length:** 0.156 inches first shoulder and 0.158 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: 0.078 inches Thready Qty Per Inch (tpi): 40 **Shoulder Shape:** Round first shoulder **Special Features:** Non-magnetic; threads undercut for relief, 0.036 in. Wide x 0.086 in. Dia.; shoulder undercut for relief, 0.031 in. Wide x 0.114 in. Dia. Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response or astm a582 assn standard single material response **Thread Series Designator:** Unc Shelf Life: N/a

**Demilitarization:** No

**Unit Of Measure:** 

## **NSN 5305-01-416-7381** Shoulder Screw - Page 2 of 2



Fiig:

A003b0