

View Online at <https://aerobasegroup.com/nsn/5305-01-417-1982>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.595 inches and 0.625 inches

Fastener Length:

Between 1.350 inches and 1.370 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.729 inches and 0.750 inches

Head Height:

Between 0.302 inches and 0.312 inches

Shoulder Diameter:

0.496 inches first shoulder and 0.498 inches first shoulder

Shoulder Length:

0.745 inches first shoulder and 0.755 inches first shoulder

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

0.250 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 43.0 rockwell c

Shoulder Shape:

Round first shoulder

Color:

Olive drab or bronze

Material:

Steel comp 4037 or steel comp 4137 or steel comp 4140 or steel comp 8630 or steel comp 8740

Surface Treatment:

Zinc or chromate

Surface Treatment Specification:

171, 1.9.2.3 military standard all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0