NSN 5305-01-417-2447

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-417-2447

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.745 inches
Fastener Length:
Between 0.845 inches and 0.875 inches
Head Style:
Watertight
Head Diameter:
Between 0.473 inches and 0.517 inches
Head Height:
Between 0.162 inches and 0.175 inches
Locking Feature:
Patch or pellet or strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Features Provided:
O ring
Thready Qty Per Inch (tpi):
20
Screw Material:
Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Locking Feature Material:
Locking Feature Material: Plastic polyamide
-
Plastic polyamide
Plastic polyamide Screw Material Specification:
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment:
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification:
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features:
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: O-ring material: silicone rubber comp a per mil-s-82496
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: O-ring material: silicone rubber comp a per mil-s-82496 Thread Series Designator:
Plastic polyamide Screw Material Specification: Qq-s-763 federal specification all material responses or astm a493-73 assn standard all material responses Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Special Features: O-ring material: silicone rubber comp a per mil-s-82496 Thread Series Designator: Unc

--

NSN 5305-01-417-2447

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-82496 spec.