

View Online at <https://aerobasegroup.com/nsn/5305-01-417-3941>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

1.188 inches

**Head Style:**

Knurled no. 5

**Head Diameter:**

0.625 inches

**Head Height:**

0.500 inches

**First Diameter From Head:**

0.175 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.688 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Criticality Code Justification:**

Zzzy

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Item must comply with requirements of defense supply center philadelphiaproduction standard no. Po0387nrp

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Special Test Features:**

Special quality control testing

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Departure From Cited Document:**

As modified by material

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0