NSN 5305-01-417-3941

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-417-3941 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.188 inches **Head Style:** Knurled no. 5 **Head Diameter:** 0.625 inches **Head Height:** 0.500 inches **First Diameter From Head:** 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.688 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity: Special Features:** Item must comply with requirements of defense supply center philadelphiaproduction standard no. Po0387nrp Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Special Test Features:** Special quality control testing **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Departure From Cited Document:

As modified by material

NSN 5305-01-417-3941

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0