NSN 5305-01-417-3942



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-417-3942 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** 1.937 inches **Head Style:** Knurled no. 5 **Head Diameter:** 0.750 inches **Head Height:** 0.438 inches **First Diameter From Head:** Between 0.235 inches and 0.240 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.499 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Special Test Features:** Special quality control testing **Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Departure From Cited Document:

As modified by material

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

NSN 5305-01-417-3942

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0